

SAFETY DATA SHEET

Date issued: 12-Nov-15

Monarch Synlube Sel 5W20

SECTION 1: PRODUCT IDENTIFICATION

Product Name Monarch Synlube Sel 5W20

Product Code # 138D

CAS # Not applicable for mixtures

ManufacturerRoyal Mfg Co, LPSynonymNot applicableChemical NameNot applicableChemical FormulaNot applicable

Trade Secret No

Address 516 S. 25th West Ave.

Tulsa, OK 74127

Phone (918) 584-2671

Emergency Contact CHEMTREC (24 hour Emergency Telephone), call: 1-800-424-9300

International CHEMTREC, call: 1-800-255-3924

Recommended Use Engine Oil

Restrictions on Use This product must not be used in applications other than recommended in

Section 1 without taking the advice from supplier/manufacturer.

SECTION 2: HAZARD(S) IDENTIFICATION

Classifications: Aquatic Hazard – Acute: Category 3

Aquatic Hazard - Long-term: Category 4

Pictograms: None Signal Word: None

Hazard Statements: Harmful to aquatic life.

May cause long lasting harmful effects to aquatic life.

Precautionary P101: If medical advice is needed have product container or label at hand **Statements:** P102: Keep out of reach of children

P102: Read Label before use

P210: Keep away from Heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

P211: So not spray on an open flame or other ignition source.

P232: Protect from Moisture.
P233: Keep container tightly closed
P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P404: Store in a closed container

Percent of the mixture consisting of ingredient(s) of unknown toxicity:

None

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Royal Mfg Co LP, P.O. Box 3308, Tulsa, OK 74101 | 918-584-2671 | www.royalmfg.com | Product Code: 138D Revision Date: June 2015 Page 1 of 5

Date issued: 12-Nov-15

Chemical Designation % of Comp. CAS No.

Distillattes (petroleum), hydrotreated light 5 - 25% 64742-55-8 paraffinic 5 - 25% 64742-54-7 Distillates (Petroleum), hydrotreated heavy 1 - 5% 84605-29-8 paraffinic < 1.0% Trade secret Zinc Alkyldithiophosphate < 1.0% 8001-22-7 Alkarvl Amine < 1.0% Not determined < 0.1% 122-39-4

Carboxylic Ester Sodium Sulfonate Diphenylamine

SECTION 4: FIRST AID MEASURES

Eyes: Flush eyes with water for at least 15 minutes. If irritation persists, seek medical attention.

Skin: Immediately remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15

minutes. Call a physician immediately.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration using a

pocket mask type resuscitator. Call a physician immediately.

Ingestion: Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious

person.

SECTION 5: FIRE FIGHTING MEASURES

Fire Hazard: No

Flash Point °C (°F): > 93.0° (199.4°)

Flammable Limits: LOWER: Not determined UPPER: Not determined

Extinguishing Media: Water Mist

Foam Dry Powder CO2

CO2

Special protective Equipment Not determined

and firefighting procedures:

Unusual Fire & Explosion: Not determined

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged container or

Precautions: spilled material unless wearing appropriate protective clothing/equipment. Ventilate the closed area.

Spills / Leaks: Isolate the spill/leak area in all directions for about 50 meters (150 ft) for liquids and about 25 meters (75 ft)

for solids and semi-solids. Eliminate all ignition sources (no smoking, flares, sparks/flames in close vicinity).

Keep unauthorized persons away and ventilate closed space before entering

SECTION 7: HANDLING & STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding

unnecessary exposure and prompt removal of material from eyes skin and clothing.

Storage: Store in a sealed container in a cool, dry environment.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

OSHA Permissible 5 mg/m³

Exposure Limits (PELs):

Threshold Limit Values 10 mg/m³

(TLVs):

Engineering Controls:

Royal Mfg Co LP, P.O. Box 3308, Tulsa, OK 74101 | 918-584-2671 | www.royalmfg.com | Product Code: 138D Revision Date: June 2015 Page 2 of 5

Date issued: 12-Nov-15

N/A

Personal Protective Equipment:

Face:

Eyes: Safety Glasses **Skin:** Gloves

Respiratory:

Pictograms:



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber Liquid **Upper Flammability/Explosive Limit:** Not determined Odor: Petroleum Lower Flammability/Explosive Limit: Not determined Odor Threshold: Not determined **Vapor Pressure:** Not determined pH: Not determined Vapor Density: Not determined Melting Point °C (°F): Not determined Vapor Temperature °C (°F): Not determined

Freezing Point °C (°F): Not determined Relative Density/Specific Gravity: 0.8480

Pour Point °C (°F): -30.0° (-22.0°) Solubility: Not Water Soluble

Boiling Range: N/A **Partition Coefficient:** Not determined **Flash Point °C (°F):** > 199.4° (93.0°) **Auto-ignition temperature:** Not determined

Flash Point Method ASTM D92 Decomposition temperature: Not determined

used:

Evaporation Rate: Not determined Viscosity (cSt): 8.00 @ 100° C

Flammability: None **VOC Content:** N/A

VOC Less Water & Exempts: N/A

SECTION 10: STABILITY AND REACTIVITY

Chemical Reactivity: Not determined

Chemical Stability: Stable under normal ambient temperature and conditions. **Conditions to Avoid:** Extreme temperature and direct sunlight/heat/flame

Materials to Avoid: Strong oxidizing agents

Hazardous Decomposition: Not expected

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation

Description of effects from short- and long-term exposure:

Not known

Description of symptoms:

Not known

Measure of toxicity:

Not known

Ingestion

Description of effects from short- and long-term exposure:

Not known

Description of symptoms: May cause nausea and vomiting.

Measure of toxicity:

Not known

Eyes

Description of effects from short- and long-term exposure:

Not known

Royal Mfg Co LP, P.O. Box 3308, Tulsa, OK 74101 | 918-584-2671 | www.royalmfg.com | Product Code: 138D Revision Date: June 2015 Page **3** of **5**

Date issued: 12-Nov-15

Description of symptoms:

Contact may cause eye irritation.

Measure of toxicity:

Not known

Skin

Description of effects from short- and long-term exposure:

Not known

Description of symptoms:

Prolonged or repeated skin contact may cause irritation.

Measure of toxicity:

Not known

Carcinogens listing:

NTP: No IARC: No OSHA: No GHS: No

Chronic Toxicity: No

SECTION 12: ECOLOGICAL INFORMATION

Aquatic Toxicity: No data available Biodegradability: No data available Bioaccumulation: No data available

SECTION 13: DISPOSAL CONSIDERATION

Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations. Regulations may vary by location.

SECTION 14: TRANSPORT INFORMATION

UN Number:

Proper Shipping Name: Monarch Syn Select 5W-20 SN/GF-5

Pictograms:

SECTION 15: REGULATORY INFORMATION

OSHA Regulated Hazard: No DOT Regulated: No

E C Classification: Non-applicable

TSCA Status: In compliance with TSCA inventory requirements for commercial purposes

SARA 312 Regulated Chemical(s): No SARA 313 Regulated Chemical(s): Yes

EPA Registration Number: Non-applicable

 California Prop. 65:
 Toluene
 0.003323%

 Benzene
 0.000086%

Naphthalene 0.000085% Ethyl benzene 0.000001%

PA Right to know Chemical(s): None known


Royal Mfg Co LP, P.O. Box 3308, Tulsa, OK 74101 | 918-584-2671 | www.royalmfg.com | Product Code: 138D Revision Date: June 2015 Page **4** of **5**

Date issued: 12-Nov-15

NJ Right to know Chemical(s): None known
Additional State Regulations: None known
Canada: Non-applicable

SECTION 16: OTHER INFORMATION





The above Information is based on the present state of our knowledge of the product at the time of publication. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy themselves that the product is entirely suitable for their purposes.

DISCLAIMER This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by N/A to be dependable and is accurate to the best of the company's knowledge. The information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. N/A assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

Royal Mfg Co LP, P.O. Box 3308, Tulsa, OK 74101 | 918-584-2671 | www.royalmfg.com | Product Code: 138D Revision Date: June 2015 Page **5** of **5**

