



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLfi.net

SL-BGGHF-32

Synthetic Biodegradable Hydraulic Fluid

SL-BGGHF-32 utilizes advanced synthetic base fluids and additives to provide biodegradability without sacrificing performance. This advanced-technology formulation has a long fluid life, even in severe operating conditions. It also offers excellent resistance against wear, corrosion and carbon deposits.

ATTRIBUTES

- Protects against wear, rust and corrosion
- Readily separates from water
- Oxidative stability
- High viscosity index
- Controls carbon and varnish formation
- Low volatility
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

SL-BGGHF-32 Viscosities	22	32	46	68
Viscosity cP @ 0°C	171	350	592	929
Viscosity cSt @ 40°C	20	33	44.9	63.9
Viscosity cSt @ 60°C	10.2	15.7	20.0	27.8
Viscosity cSt @ 80°C	6.1	8.8	10.7	14.2
Viscosity cSt @ 100°C	4.0	5.6	6.6	8.5
Flash Point °F (°C)	385 (196)	435 (224)	442 (228)	456 (236)
Demulsibility	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion	1a	1a	1a	1a
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0