



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLFi.net

SL-32GR

Synthetic Compressor Lubricant

SL-32GR offers full compatibility with most OEM polyalkylene glycol (PAG) compressor lubricants. This compatibility means that flushing of the existing compressor oil is not necessary to change to SL-32GR, reducing maintenance costs and downtime. SL-32GR offers superb resistance against water contamination and an extended service life of 8,000 hours.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

| SL-32GR Viscosities | 32 | 46 | 68 |
|----------------------------|-----------|-----------|-----------|
| Viscosity cSt @ 0°C | 344 | 699 | 990 |
| Viscosity cSt @ 40°C | 32 | 46.1 | 67 |
| Viscosity cSt @ 60°C | 15.2 | 19.9 | 28.4 |
| Viscosity cSt @ 80°C | 8.5 | 10.5 | 14.7 |
| Viscosity cSt @ 100°C | 5.4 | 6.6 | 8.7 |
| Flash Point °F (°C) | 435 (224) | 465 (241) | 478 (247) |
| Copper Corrosion | 1a | 1a | 1a |
| Rust Test: Distilled Water | Pass | Pass | Pass |
| Rust Test: Salt Water | Pass | Pass | Pass |
| Foam Sequence I, II, III | 0/0/0 | 0/0/0 | 0/0/0 |