



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLFi.net

SL-46GR

Synthetic Compressor Lubricant

SL-46GR offers full compatibility with most OEM polyalkylene glycol (PAG) compressor lubricants. This compatibility means that flushing of the existing compressor oil is not necessary to change to SL-46GR, reducing maintenance costs and downtime. SL-46GR offers superb resistance against water contamination and an extended service life of 8,000 hours.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

SL-46GR Viscosities	46
Viscosity cSt @ 0°C	699
Viscosity cSt @ 40°C	46.1
Viscosity cSt @ 60°C	19.9
Viscosity cSt @ 80°C	10.5
Viscosity cSt @ 100°C	6.6
Flash Point °F (°C)	465 (241)
Copper Corrosion, 24 Hr	1a
Rust Test: Distilled Water	Pass
Rust Test: Salt Water	Pass
Foam Sequence I, II, III	0/0/0