



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLFi.net

SL-GR68

Synthetic Compressor Lubricant

SL-GR68 offers full compatibility with most OEM polyalkylene glycol (PAG) compressor lubricants. This compatibility means that flushing of the existing compressor oil is not necessary to change to SL-GR68, reducing maintenance costs and downtime. SL-GR68 offers superb resistance against water contamination and an extended service life of 8,000 hours.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

SL-GR68 Viscosities	32	46	68
Viscosity cSt @ 0°C	344	699	990
Viscosity cSt @ 40°C	32	46.1	67
Viscosity cSt @ 60°C	15.2	19.9	28.4
Viscosity cSt @ 80°C	8.5	10.5	14.7
Viscosity cSt @ 100°C	5.4	6.6	8.7
Flash Point °F (°C)	435 (224)	465 (241)	478 (247)
Copper Corrosion	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0