



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - [www.SLFi.net](http://www.SLFi.net)

# SL-HTF-DE-32

## Synthetic Heat Transfer Fluid and Cleaner

SL-HTF-DE-32 is made with the finest thermally and oxidatively stable synthetic base fluids. It is further enhanced with proprietary additives that are designed to dissolve carbon and varnish. It is designed to operate at longer, higher temperatures than other synthetic fluids. SL-HTF-DE-32 is non-toxic and non-hazardous, and it will not form carbon in most applications.

### ATTRIBUTES

- Meets FDA, USP and NF standards
- High viscosity index
- No odor
- 21 CFR 573.680 use in animal feed
- High degree of purity
- Meets USDA requirements

### TYPICAL LUBRICANT PROPERTIES

<b>SL-HTF-DE-32 Viscosities</b>	<b>40</b>
Viscosity Index	96
Viscosity cSt @ 0°C	541
Viscosity cSt @ 40°C	42
Viscosity cSt @ 60°C	18.9
Viscosity cSt @ 80°C	10.2
Viscosity cSt @ 100°C	6.3
Viscosity cSt @ 120°C	4.3
Flash Point °F (°C)	438 (226)
Demulsibility, 54.4°C, 30 Min	40/40/0
Copper Corrosion, 24 Hr	1a
Foam Sequence I, II, III	0/0/0