



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLfi.net

SL-PLL-FG-CL

Synthetic Food Grade Picket Line Lubricant with Cleaner

PLL-FG-CL is a premium, synthetic, light viscosity, general purpose lubricant that meets 21 CFR 178.3570 H1 requirements (lubricants with incidental food contact).and ISO 21469,

PLL-FG-CL is made from advance technology synthetic base materials and cleaners to free stuck parts, clean, and provide long lasting, non-gumming lubrication. PLL-FG-CL removes surface rust and other deposits. It also lubricates then stays in place to help protect metal parts from rust and corrosion.

ATTRIBUTES

- Outstanding stability
- Excellent water separation
- Low volatility
- High flash point
- Excellent rust control
- Advanced cleaning properties

TYPICAL LUBRICANT PROPERTIES

SL-PLL-FG-CL Viscosities	PLL-FG-/CL
Viscosity Index	103
Viscosity cSt @ 40°C	12.7
Viscosity cSt @ 100°C	3.1
Flash Point °F (°C)	370 (188)
Copper Corrosion, 24 Hr.	1a
Rust test	Pass
Demulsibility, 130°F, 30 Min	40/40/0