



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLfi.net

SL-SF68FG

Spiral Freeze Synthetic Food Grade Low Temp Gear Fluid

6531 is designed for use in a wide range of gear applications. It is formulated to provide a long oil life with excellent oxidative stability, film strength, lubricity and wear protection. It offers outstanding protection, even in the most demanding applications.

ATTRIBUTES

- Excellent lubricity
- High film strength
- Long oil life
- Controls carbon and varnish formation
- Superior dispersant properties
- Resists water contamination
- Protects against rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

SL-SF68FG Viscosities	32	46	68
Viscosity cSt @ 40°C	32	46	70
Viscosity cSt @ 100°C	5.6	7.2	9.7
Viscosity Index	114	117	119
Flash Point °F (°C)	420 (215)	440 (226)	450 (232)
Pour Point °F (°C)	-55 (-48)	-52 (-46)	-49 (-45)
Timken OK Load, Kg	40	40	40
Copper Corrosion, 24 Hr	1a	1a	1a
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0