



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLFi.net

SL-SGL-220

Synthetic Gear Lubricant

SL-SGL-220, formulated with enhanced extreme-pressure (EP) additives, is designed for heavy-load and high-temperature applications. This lubricant provides excellent protection and a long oil life — even in the most demanding applications and environments.

ATTRIBUTES

- Excellent lubricity
- High film strength
- Controls carbon and varnish formation
- Long oil life
- Superior dispersant properties
- Resists water contamination
- Protects against wear, rust and corrosion

TYPICAL LUBRICANT PROPERTIES

SL-SGL-220 Viscosities	100	150	220
Viscosity cSt @ 0°C	1655	2868	4547
Viscosity cSt @ 40°C	96	153	220
Viscosity cSt @ 60°C	38.7	59.1	81.7
Viscosity cSt @ 80°C	19.2	28.2	37.7
Viscosity cSt @ 100°C	11.2	15.7	20.4
Viscosity Index	102	105	103
Flash Point °F (°C)	500 (266)	510 (266)	515 (268)
Timken OK Load, Kg	40	40	40
Copper Corrosion, 24 Hr	1b	1b	1b
Demulsibility, 130°C, 30 Min	40/39/1	40/39/1	40/39/1