



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - [www.SLFi.net](http://www.SLFi.net)

# SL-SGLX-100

## Synthetic Non-EP Gear Lubricant

SL-SGLX-100 is designed for use in a wide range of gear applications. It is formulated to provide a long oil life with excellent oxidative stability, film strength, lubricity and wear protection. It offers outstanding protection — even in the most demanding applications.

### ATTRIBUTES

- Excellent lubricity
- High film strength
- Long oil life
- Controls carbon and varnish formation
- Superior dispersant properties
- Resists water contamination
- Protects against rust and corrosion
- Non-toxic/non-hazardous

### TYPICAL LUBRICANT PROPERTIES

<b>SL-SGLX-100 Viscosities</b>	<b>68</b>	<b>100</b>
Viscosity cSt @ 40°C	70	102
Viscosity cSt @ 100°C	9.7	12.8
Viscosity Index	119	121
Flash Point °F (°C)	450 (232)	500 (260)
Pour Point °F (°C)	-49 (-45)	-48 (-44)
Timken OK Load, Kg	40	40
Copper Corrosion, 24 Hr	1a	1a
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0