



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLfi.net

# SL-SVAC FG 22

## Synthetic Vacuum Pump Lubricant - Food Grade

SL-SVAC FG22 is designed to provide excellent service and a long life in Liquid Ring vacuum pumps. It has a very low vapor pressure, very high oxidative resistance, and excellent thermal and shear stability. SL-SVAC FG22 protects against wear, rust, and corrosion.

SL-SVAC FG22's advanced-technology additive system protects vacuum pumps from varnish, carbon and sludge deposits. It exceeds the requirements of DIN 51506 VD-L standards and meets H1 requirements for incidental food contact.

### ATTRIBUTES

- Food grade formulation
- Very low vapor pressure
- Excellent thermal and chemical stability
- Excellent carbon, varnish, wear and corrosion control
- Low volatility
- Excellent film strength

### TYPICAL LUBRICANT PROPERTIES

SL-SVAC FG 22 Viscosities	SL-SVAC FG 22
Viscosity Index	105
Viscosity cSt @ 0°C	202
Viscosity cSt @ 40°C	23
Viscosity cSt @ 60°C	11.6
Viscosity cSt @ 80°C	6.8
Viscosity cSt @ 100°C	4.5
Flash Point °F (°C)	399 (264)
Demulsibility, 130°F, 30 min	40/40/0
Copper Corrosion 24 Hr	1a
Rust Test	Pass
Foaming	0/0/0