



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - [www.SLfi.net](http://www.SLfi.net)

# 6886

## SL Universal PHE

6886 is formulated to provide complete compatibility with a wide variety of OEM and aftermarket rotary screw compressor lubricants. Flushing is not required to switch to 6886; in most cases, it can be added directly on top of the existing compressor oil. Its advanced formulation helps avoid costly lubricant-contamination mistakes and helps streamline product inventory. 6886 is also formulated to provide outstanding resistance against wear, rust, corrosion and sludge buildup, and to provide 8,000+ hours of service.

Top-off compatible with:

- PAG-based compressor lubricants
- POE-based compressor lubricants
- Diester-based compressor lubricants
- PAO-based compressor lubricants
- Partial-, semi- and petroleum-based compressor lubricants

### ATTRIBUTES

- Universal formulation, compatible with most OEM and aftermarket rotary screw air compressor lubricants
- 8,000+ hours of oil life at 100°C discharge temperature
- Oxidatively and thermally stable
- High flash point
- Controls carbon and varnish formation
- Low volatility
- Excellent film strength
- Non-toxic/non-hazardous

### TYPICAL LUBRICANT PROPERTIES

<b>6886 Viscosities</b>	<b>46</b>
Viscosity cSt @ 40°C	46
Viscosity cSt @ 100°C	7.7
Viscosity Index	135
Flash Point °F (°C)	468 (242)
Auto-Ignition Point °F (°C)	725 (385)
Pour Point °F (°C)	-34 (-37)
Copper Corrosion	1a
Demulsibility	40/39/1