



Synthetic Lubricants & Filters, inc. - World Headquarters - 7401 University Dr., Shreveport, LA 71105
Phone: 855-215-2740, 855-215-2741, 318-779-1248 / Emergency Phone: 800-637-5126 / Fax: 318-779-1762 - www.slfi.net

SLWBPB-500

Performance Boost

SLFI's SLWBPB-500 Performance Boost is an additive which when added to High Water Based Fluids significantly increases the lubricity, wear and corrosion protection of these fluids without adversely affecting their operating characteristics. It greatly extends pump life and reduces wear and downtime. SLWBPB-500 is biodegradable and when mixed with High Water based fluids and is also fire resistant.

SLWBPB-500 is compatible with all High Water Based Fluids and is normally added at 1 part boost to 10 parts HWBF.

TYPICAL PROPERTIES

Lubrication Properties	SWBPB-500
Appearance	Clear Amber Tint
Ph	7
Specific Gravity @15.6 °C	.86
Viscosity cSt @ -20 °C	152
Viscosity cSt @ 0 °C	42
Viscosity cSt @ 40 °C	8.5
Pour Point °C	> -40

MATERIAL COMPATIBILITY

SLFI's SLWBPB-500 Performance Boost contains performance additives which ensure high levels of compatibility with materials typically used with HWBF systems.

- Ferrous Metals: Compatible
- Non Ferrous Metals: Compatible
- Packaging and Seal Materials: Compatible with normal hydraulic systems components