



Synthetic Lubricants & Filters, inc. - World Headquarters - 7401 University Dr., Shreveport, LA 71105  
Phone: 855-215-2740, 855-215-2741, 318-779-1248 / Emergency Phone: 800-637-5126 / Fax: 318-779-1762 - [www.slfi.net](http://www.slfi.net)

## ***SLWBPB-500*** ***Performance Boost***

SLFI's SLWBPB-500 Performance Boost is an additive which when added to High Water Based Fluids significantly increases the lubricity, wear and corrosion protection of these fluids without adversely affecting their operating characteristics. It greatly extends pump life and reduces wear and downtime. SLWBPB-500 is biodegradable and when mixed with High Water based fluids and is also fire resistant.

SLWBPB-500 is compatible with all High Water Based Fluids and is normally added at 1 part boost to 10 parts HWBF.

### ***TYPICAL PROPERTIES***

Lubrication Properties	SWBPB-500
Appearance	Clear Amber Tint
Ph	7
Specific Gravity @ 15.6 °C	.86
Viscosity cSt @ -20 °C	152
Viscosity cSt @ 0 °C	42
Viscosity cSt @ 40 °C	8.5
Pour Point °C	> -40

### ***MATERIAL COMPATIBILITY***

SLFI's SLWBPB-500 Performance Boost contains performance additives which ensure high levels of compatibility with materials typically used with HWBF systems.

- Ferrous Metals: Compatible
- Non Ferrous Metals: Compatible
- Packaging and Seal Materials: Compatible with normal hydraulic systems components



SLWBPB-500 - Revised 01/2012

The information on SLFI and competitive products provided should only be used as a general guide. Lubricant properties are typical results and should not serve as a sole resource for determining the correct lubricant for a particular application. Please consult a SLFI representative to ensure that the product is the correct choice for the application.